

Release Notes

Essentials Gen 4 Cameras

Product Code	Model Name	Firmware
IES02-D10-OI04	Essentials Gen 4, 2MP Dome, 2.8mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.01.00.3811
IES02-D12-OI04	Essentials Gen 4, 2MP Dome, 2.7-13.5mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.01.00.3811
IES02-B10-BI04	Essentials Gen 4, 2MP Bullet, 2.8mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.01.00.3811
IES02-B12-BI04	Essentials Gen 4, 2MP Bullet, 2.7-13.5mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.01.00.3811

Product Data

Visit the IP Cameras section of our web site, www.illustracameras.com, to download datasheets and other documentation in PDF format.

November 2020

Note

In case of discrepancy, the information in this document supersedes the information in any document referenced herein.

© 2020 Tyco Security Products. All rights reserved.

8200-1929-04 B0

JOHNSON CONTROLS, TYCO and ILLUSTRa are trademarks and/or registered trademarks.
 Unauthorized use is strictly prohibited
 © 2020 Johnson Controls. All rights reserved.

Table of Contents

What's in This Release	3
What's New	3
Previous Firmware	3
Features	4
Firmware Upgrade	5
Upgrade Camera Firmware through the Web GUI	5
<i>Procedure: Upgrade Camera Firmware through the Web GUI</i>	5
Upgrade Camera Firmware through Illustra Connect	5
Features	6
Enhanced Security	6
<i>Security Modes Summary</i>	6
<i>Username and Password Complexity Requirements</i>	7
Changes in Enhanced security profile.....	8
Analytics	8
Stream Tables	9
Known Limitations and Issues	11
Server Integration Limitations	14
Contact Information	15

What's in This Release

What's New

Firmware illustra.Ess4.01.01.00.3811 introduces the following:

- Corridor mode support
- CIFS feature
- Support added for Cloudvue services
- Support added for third stream

Note: If upgrading to this firmware a factory reset is required to fully initiate new features

Previous Firmware

Firmware illustra.Ess4.01.00.00.2845

Introduces the new Essentials Gen 4 2MP camera models.

Product Code	Model Name	Firmware
IES02-D10-OI04	Essentials Gen 4, 2MP Dome, 2.8mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.00.00.2845
IES02-D12-OI04	Essentials Gen 4, 2MP Dome, 2.7-13.5mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.00.00.2845
IES02-B10-BI04	Essentials Gen 4, 2MP Bullet, 2.8mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.00.00.2845
IES02-B12-BI04	Essentials Gen 4, 2MP Bullet, 2.7-13.5mm, Outdoor, vandal, clear, white, TDN w I/R	Ess4.01.00.00.2845

Key Features

- High resolution, 2 megapixel images, Multiple IP streams of H.264, H.265, and MJPEG video
- Integration with VideoEdge NVR, VideoEdge Hybrid, victor Unified Client, ExacqVision recorders and Clients
- Integration with Illustra Connect v 3.2 and above
- Illustra API v3.4
- ONVIF 2.4 profile S compliant
- Power over Ethernet (PoE) or AC powered (model specific)
- Motion Detection and Blur Detection support on camera
- Wide Dynamic Range, TWDR
- Auto & Manual White Balance Modes
- Lens calibration
- Manual Focus and Zoom Control (model specific)
- One touch Focus (model specific)
- Eventing with RTP meta-data streaming
- Support for up to nine Regions of Interest
- Support for up to eight Privacy Zones
- Enhanced Security
- SD card event buffering (requires micro-SD or SD-HC card)
- SD card event download
- Outstanding color reproduction
- No dependencies on 3rd Party Utilities for Camera Setup (No QuickTime and Java requirements)
- Expanded Browser Support: IE, Chrome, Firefox, Safari
- UPnP Discovery
- Easy to install
- Sleek and compact design
- Support for FTP, SNMP, SMTP, CIFS, 8021.x and Firewall filtering
- Cloudvue Integration

Firmware Upgrade

You can upgrade the Illustra Essentials Camera through the camera web GUI or by using Illustra Connect.

Upgrade Camera Firmware through the Web GUI

NOTE:

All camera settings are maintained after you upgrade the camera firmware. It is recommended to clear your browser cache after a firmware upgrade.

Procedure: Upgrade Camera Firmware through the Web GUI

1. Using Internet Explorer connect to the camera via the IP Address and login to the Web GUI.
2. Select **Setup** from the web banner to access the setup menus.
3. Select **Maintenance** from the **System** menu and identify the **Camera Upgrade** section.
4. Select **Browse**. The Choose file dialog displays.
5. Navigate to the location where the firmware file has been saved. Select the firmware file then select the **Open** button.
6. Select **Upload**. The file transfer begins and a progress bar displays.

Upgrade Camera Firmware through Illustra Connect

NOTE:

All camera settings are maintained after you upgrade the camera firmware.

Procedure: Update Camera Firmware through Illustra Connect

1. Install and launch the Illustra Connect software utility.
2. From the displayed list of cameras; right-click on the camera requiring the software upgrade.
3. Select **Upgrade Firmware**. The Firmware Upload window will display.
4. Select **Choose File** and browse to the firmware upgrade file.
5. Select **Upgrade** to start the upgrade.

Features

Accessing the Illustra Essentials Series Camera Web User Interface

1. Select a supported browser and navigate to the camera IP address.
2. When you select the camera, the sign in page is displayed.
3. Select your preferred language from the drop-down menu. The default language is English.
4. Enter the default username and password when prompted - Username: admin, Password: admin.
5. Click **Log in**. The camera Web User Interface is displayed. The first time that you access the camera, or after a factory reset, you are prompted to **Define a Host ID** and **Select a Security Type**.

Define a Host ID: The admin user must enter a 6 character code for the Host ID that includes both letters and/or numbers. This unique password is used to access the operating system files. The HostID is not stored on the camera for security reasons and must be presented to Illustra Technical Support when remote access to the operating system is required.

Select a Security Type: Standard Security or Enhanced Security. If you are keeping Standard Security, it is best practice to select the Change Password check box to immediately change the default password to one unique to your surveillance system.

6. Optional - If you select the Enhanced Security option, you are required and instructed to create a complex password.

See below for further information on Security configuration.

Accessing the Illustra Essentials Series Camera Web User Interface for the first time

1. Select a supported browser and navigate to the camera IP address.
2. When you select the camera, the sign in page is displayed.
3. Select your preferred language from the drop-down menu. The default language is English.
4. Enter the default username and password when prompted - Username: admin, Password: admin.
5. Click **Log in**. The camera Web User Interface is displayed. The first time that you access the camera, or after a factory reset, you are prompted to **Define a Host ID** and **Select a Security Type**.

Define a Host ID: The admin user must enter a 6 character code for the Host ID that includes both letters and/or numbers. This unique password is used to access the operating system files. The HostID is not stored on the camera for security reasons and must be presented to Illustra Technical Support when remote access to the operating system is required.

Select a Security Type: Standard Security or Enhanced Security. If you are keeping Standard Security, default admin password change is **enforced**.

6. Optional - If you select the Enhanced Security option, you are required and instructed to change the username and create a complex password.

See below for further information on Security configuration.

Enhanced Security

The Enhanced Security feature intends to advance the security of the Illustra cameras by enforcing security best practices and adding features to allow the installer and end-users to customize the camera's security to meet their controls.

Security Modes Summary

Standard Security

1. Default admin password change is enforced.
2. Changes to communication protocols is available to all users with appropriate privileges.
3. Passwords complexity is set to require minimum of any 5 characters (admin cannot be used).
4. Authentication Method is set to basic by default.

Enhanced Security

1. Unsecure Protocols are disabled by default until enabled by a user.
2. Discovery Protocols are disabled by default until enabled by a user.
3. Changes in the protocols will only be available to a user with administrative privileges and require that user to re-enter their password.
4. Default admin username & password change is enforced.
5. Usernames for all accounts must meet the Username Password Complexity Requirements, which are detailed below.
6. Passwords for all accounts must meet the Password Complexity Requirements, which are detailed below.
7. Authentication Method is set to HTTPS Digest by default (HTTP disabled).

Note: When applying Enhanced security all these changes will be done automatically, but if changing from Enhanced to Standard the settings will not be changed automatically – to reset to standard profile user will need to do changes manually or factory reset camera and select standard Security when prompted.

Username and Password Complexity Requirements

Username Complexity for Enhanced Security Mode:

- a. Minimum characters: 5

Password Complexity for Enhanced Security Mode:

- a. Minimum characters: 8
- b. Have least one character from each of the following character groups:
 - i. upper case letters ABCDEFGHIJKLMNOPQRSTUVWXYZ
 - ii. lower case letters abcdefghijklmnopqrstuvwxyz
 - iii. numeric characters 0123456789
 - iv. Special characters @ % + \ / ' ! # \$ ^ ? : , () { } [] ~ - _ `
- c. The password cannot contain the username.

Default admin/admin & Automatic prompt for username and password change at first login

The admin/admin user is hardcoded until security mode is selected on first login.

For Standard Security

Password change is mandatory after first login.

New Password should be a minimum of five characters long.

New Password cannot be admin.

For Enhanced Security

When selected, a pop up is visible requiring you to change your username and password.

- **A username & password change is mandatory** – Note: If the user sets a new username and password – admin/admin is automatically replaced.
- Certain criteria apply to both the username and password (See Username and Password complexity).

NOTE:

When Enhanced Security is enabled the user is prompted to change the username and password from the default admin/admin. If not all rules are applied then the change request is denied and credentials remain as admin/admin. Failure to comply by rules, intermittently may result in camera log in being unavailable for a few minutes to allow camera to restore default functionality.

How to restore admin/admin:

1. Restore factory default camera.

Changes in Enhanced security profile

When changing security to 'enhanced', the camera performs the following changes:

- Admin/admin password automatically replaced by new Enhanced username/password.
- Change from basic to Digest HTTPs authentication.
- Enables RTSP authentication.
- Disables all ONVIF capabilities.

Note: When applying Enhanced security all these changes will be done automatically, but if changing from Enhanced to Standard the settings will not be changed automatically – to reset to standard profile user will need to do changes manually or factory reset camera and select standard Security when prompted.

Analytics

	Motion Detection Metadata	Motion Detection Events	Blur Detection Events
Illustra Essentials Gen 4 2MP Outdoor Domes	No	Yes	Yes
Illustra Essentials Gen 4 2MP Outdoor Bullet	No	Yes	Yes

Stream Tables

Essentials 2MP camera stream table

		Normal Mode			
		Resolution	Description	Max FPS	
				TWDR Off	TWDR
Stream 1	H264	1920 x 1080	(1080p) 16:9	30	30
	H265	1600 x 900	(HD+) 16:9	30	30
	H264 Intellizip	1280 x 720	(720p) 16:9	30	30
	H265 Intellizip	1024 x 576	(PAL+) 16:9	30	30
	MJPEG	960 x 540	16:9	30	30
		800 x 480	16:9	30	30
		640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30
320 x 180	16:9	30	30		
Stream 2	H264	1920 x 1080	(1080p) 16:9	30	30
	H265	1600 x 900	(HD+) 16:9	30	30
	H264 Intellizip	1280 x 720	(720p) 16:9	30	30
	H265 Intellizip	1024 x 576	(PAL+) 16:9	30	30
	MJPEG	960 x 540	16:9	30	30
		800 x 480	16:9	30	30
		640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30
320 x 180	16:9	30	30		
Stream 3	H264	1280 x 720	(720p) 16:9	30	30
	H265	1024 x 576	(PAL+) 16:9	30	30
	H264 Intellizip	960 x 540	16:9	30	30
	H265 Intellizip	800 x 480	16:9	30	30
	MJPEG	640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30
320 x 180	16:9	30	30		

Note: A maximum of three concurrent streams are supported by the camera. This includes shared streams.

		Corridor Mode			
		Resolution	Description	Max FPS	
				TWDR Off	TWDR
Stream 1	H264 H265 H264 Intellizip H265 Intellizip	1920 x 1080	(1080p) 16:9	30	30
		1600 x 900	(HD+) 16:9	30	30
		1280 x 720	(720p) 16:9	30	30
		1024 x 576	(PAL+) 16:9	30	30
		960 x 540	16:9	30	30
		800 x 480	16:9	30	30
		640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30
Stream 2	H264 H265 H264 Intellizip H265 Intellizip	1920 x 1080	(1080p) 16:9	30	30
		1600 x 900	(HD+) 16:9	30	30
		1280 x 720	(720p) 16:9	30	30
		1024 x 576	(PAL+) 16:9	30	30
		960 x 540	16:9	30	30
		800 x 480	16:9	30	30
		640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30
Stream 3	H264 H265 H264 Intellizip H265 Intellizip	1280 x 720	(720p) 16:9	30	30
		1024 x 576	(PAL+) 16:9	30	30
		960 x 540	16:9	30	30
		800 x 480	16:9	30	30
		640 x 360	(mHD) 16:9	30	30
		480 x 270	16:9	30	30

Note: A maximum of three concurrent streams are supported by the camera. This includes shared streams.

Note: MJPEG is not a supported codec for any stream when corridor mode is enabled.

Note: Resolution 320x180 is not supported with Corridor mode. If any stream is set to 320x180, it will be updated to 480x270 when corridor mode is applied.

Known Limitations and Issues

Description	Suggested Work-Around
Applicable to all Essentials cameras: If the camera date/time has been set manually, camera date/time may not be accurate if camera has been without power for more than 24 hours	The camera should be setup with a NTP server to ensure the time is always accurate. NTP will guarantee clock sync as soon as camera is operational. If NTP is not available user should review date and time setting manually after the camera is plugged in. If the clock has reset to 1970, once the date/time page is accessed the camera will automatically sync to the machine used in the active GUI session.
Applicable to all Essentials cameras: The Frequency setting in Expo- sure can limit FPS to 25 FPS if the frame rate is set to 30 when the frequency is set to 50Hz.	If FPS needs to be set above 25FPS, Frequency should be set to 60Hz.
Applicable to all Essentials cameras: Changing Exposure settings on the camera can sometimes affect frame rate, lowering it well below what is set on the camera.	If frame rate is a priority, it is advised that Maximum Exposure is set to at least '1/30' to reach 30FPS.
Applicable to all Essentials cameras: Formatting or unmounting a SD Card is sometimes met with a 'Device is Busy' modal.	This usually means the camera is currently recording a clip to the SD Card. It is advised to wait for a period of time when no clips are being recorded or turn off recording on the camera.
Applicable to all Essentials cameras: Changing stream configurations when a clip is being recorded may cause recording to stop or the camera to reboot.	It is advised to setup your stream configurations prior to enabling Clip Record. Otherwise, please stop recording before changing stream configurations. If recording has stopped, please reboot camera.
Applicable to all Essentials cameras: Video playing through camera GUI may not be live – browser cache issue	Refresh page or clear cache.
Applicable to all Essentials cameras: If streaming to VLC and the camera undergoes a considerable time change either through factory defaulting of the unit, or manual/NTP change, the VLC video goes grey. This is a VLC application Bug – the issue does not occur on other applications or server integrations.	Restart the VLC stream or configure times prior to starting a VLC stream.
Applicable to all Essentials cameras: Under certain lights (Mercury and Sodium outdoor lighting) the user may observe that the picture does not have the correct colors.	The user can change the White Balance setting from the default 'Auto WB Normal' to 'Auto WB Wide'.

Description	Suggested Work-Around
Applicable to all Essentials cameras: When Enhanced Security is enabled the user is prompted to change the username and password from the default admin/admin. If not all rules are applied then the change request is denied and credentials remain as admin/admin. Failure to comply by rules, intermittently may result in camera log in being unavailable for a few minutes to allow camera to restore default functionality.	Ensure that all username and password rules are followed.
Applicable to all Essentials cameras: At first boot or after a factory reset the camera will sync time zone, date and time with PC used on First Login. However, the camera may select a generic time zone which will not have DST time changes associated to it or, during Daylight saving time, the time zone may be offset if using a workstation on UTC time zone (windows)	Please check the time zone is assigned correctly at initial boot or after a factory default
Applicable to all Essentials cameras: When disabling UPnP, note that the camera will still be accessible on some machines as discovery results may have been cached.	UPnP will be fully disabled when Enhanced Security is enabled, cached results will also be blocked
Applicable to all Essentials cameras: In Security status - Changing the value of Authentication will cause a service restart which will result in GUI being inaccessible for about 10 seconds	Wait 10 seconds for service to restart and GUI working again
Applicable to all Essentials cameras: Changing Video Settings when a clip is recording may produce a corrupt MP4 due to the interruption	Setup your stream settings before you enable recording.
Applicable to all Essentials cameras: When TWDR is enabled, stream configuration restrictions apply	Ensure that stream is configured correctly before enabling TWDR. See stream tables for supported configurations.
Applicable to all Essentials cameras: Exposure method position does not change when Mirror or Flip orientation is applied.	Re-configure Exposure Method after Mirror or Flip orientation is applied.
Applicable to all Essentials cameras: GUI, ONVIF and IAPI3 stream configuration combination may not always reflect the camera limitation	The camera will automatically adjust to its limitation (check the stream table for details).
Applicable to all Essentials cameras: Login page may not fully load when the user logs in using the HTTPS method through the Chrome browser.	Refresh the browser.

Description	Suggested Work-Around
Applicable to all Essentials cameras: When selecting Enhanced Security - the admin user will be required to conform to new username & password rules- the new rules will not be applied to already created user profiles - all new profiles will require to apply to these rules	If required change user and operator passwords manually
Applicable to all Essentials cameras: Clip Recording: Clips can sometimes be longer or shorter than the expected duration due to the gap between IFrames.	N/A - This is a side effect of the stream settings.
Applicable to all models: Backup/Restore: When the restoration changes the HTTP/HTTPS policy the camera may not be restored correctly.	Set the correct HTTP/HTTPS policy before restoring the file or reboot the camera after the restore.
Motion mask restriction with Exacq. Area not covered by mask must resemble one square/rectangle only.	N/A
After applying HTTPS through the Auto Configuration feature in Illustra Connect the camera status may incorrectly show as 'unresponsive' however camera is fully functional.	N/A
If the user configures a privacy zone when using flip or mirror, the privacy zone may move position after a camera reboot	Disable and re-enable privacy zone.
Changing single time or date values may update other time and date values.	Ensure time and date is configured correctly before leaving page
HTTP/HTTPS – unable to upload certificate.	N/A
Changing IP address causes web browser to close.	Open new browser and type new IP address into search bar.
Corridor mode cannot be correctly configured if it is enabled after camera is added to NVR	Enable Corridor mode before adding camera to nvr.
Enabling the 'large' OSD option may cause camera performance issues or may remove OSD from stream	Use normal OSD only. If performance issues are caused, select the 'normal' osd option and reboot camera.
Exacq motion mask issues when corridor mode is enabled, mask appears on bottom half of screen and user-drawn masks may not apply to desired position on camera	Configure motion region through camera GUI.

Server Integration Limitations

Description	Suggested Work-Around
Applicable to all Essentials cameras: Genetec Recorders do not support all the resolutions the camera supports.	N/A - This is a limitation of the recorder.
Applicable to all Essentials cameras - ONVIF Integration - Profile S Integration does not support Codec: H265.	If those codecs are required then an iAPI3 integration is necessary

Contact Information

If you have any questions regarding these release notes, please contact Tyco Security Products Technical Services at:

Toll Free: 800-507-6268, Option 2

International: 561-912-6259, Option 2

Alternative Number: 800-392-2873

Fax: 450-444-2029

Hours: 08:00 – 20:00 EST

Email: adtechservices@tycoint.com

Website: www.illustracameras.com

In Europe, Middle East and Africa, contact Technical Support at:

Toll Free: +800 CALLTYCO or +800-2255 8926

Direct: +31 475 352 722

Hours: 08:00 – 18:00 CET

Email: tsp.emea.video.support@tycoint.com

Website: www.tycosecurityproductsemea.com

Website: www.calltyco.com

Local Direct dial numbers:

UK 08701 238 787
France 0800 90 79 72
Spain 900 99 39 61
Germany 0800 1806 757
Italy 0800 874 091
Belgium 0800 76 452
Ireland 021 480 1122

Bahrain 800 04127
Greece 00800 31 229 453
Russia 810 800 20 521 031
Turkey 00800 31 923 007
United Arab Emirates 800 0310 7123
Israel 03 345 6868

In Latin America and Caribbean, contact Technical Support at:

Southern Latin America

Contact: Cesar Cristal Phone:
+54-11-4711-8711
Cell: +54911-6452-7573
Email: ccristal@tycoint.com

Brazil (South)

Contact: Dani Hissnauer Miguel
Phone: +55 (11) 2172 9224
Cell: +55 (11) 97663-2653
Email: danimiguel@tycoint.com

Brazil (North)

Contact: Wagner Soares
Phone: +55 (21) 2108-6016
x.250
Cell: +55 (21) 99153-3519
Email: wsoares@tycoint.com

Northern Latin America & Caribbean

Contact: Hildebrando Duran
Phone: +57-1638-6278
Cell: +57-317668-9590
Email: hiduran@tycoint.com

Mexico

Contact: Marco Antonio Salguero
Phone: +52-55-5488-8092
Cell: +52-55-1473-4946
Email: msalguero@tycoint.com

In Asia Pacific, contact Technical Support at:

Toll Free: +800 CALLTYCO or +800-2255 8926

Direct: +86 21 60 23 0650

China Only Hotline: 400 671 1528

India Only Hotline: 1 800 1082 008

Hours: 08:00 – 17:00 CST

Email: apac.support@tycoint.com

Information furnished by Tyco Security Products is believed to be accurate and reliable. However, no responsibility is assumed by Tyco Security Products for its use, nor any infringements of other rights of third parties which may result from its use. No license is granted by implications or otherwise under any patent rights of Tyco Security Products.
