Essentials Gen4 2MP IP Mini-Dome







Key Features

- 2MP (1080p) resolution for HD quality images
- Manage bandwidth resources with H.264 and H.265 dualstream encoding
- Dual stream recording, 1080P at 30ips to capture as much detail as possible
- · 2.8mm fixed lens
- IR Illuminators deliver clear video when viewing dark scenes
- Factory focused lens for a quick installation
- IP67 environmental rating to protect against dust and water
- IK10 vandal resistant
- True Day/Night functionality for low light conditions
- WDR to simultaneously view highcontrasting areas
- Supports corridor mode

Meet a Variety of Recording Requirements at a Low Cost

The Illustra Essentials Gen4 Mini-Dome camera provides up to 1080p resolution with IR illumination to manage low light scenes. The affordable cameras capture video in a variety of lighting conditions with features such as True Day/ Night and Wide Dynamic Range to fulfill security operators' expectations, all while maintaining a lower price point.

The camera includes the latest compression technologies by supporting both H.265 and H.264 codecs resulting in reduced bandwidth and storage requirements. To aid ease of setup all Essentials Gen4 models support one-touch auto-focus.

Rated IP67 for an additional degree of environmental protection, the Mini-Dome exceeds previous generations of Illustra Essentials cameras.

The Essential Mini-Dome also features corridor mode which allows cameras to maximize video surveillance in narrow vertical situations. Ideal for hallways, retail aisles, and tunnels this mode creates a unique high quality, vertical video.



Record Video with Low Light Clarity

Poor low-light performance by megapixel cameras hampers some of the most important tasks security professionals need to perform. Cameras that fail in low light clarity negatively impact both the necessary functions of security and cost of ownership.

The sensitive processor and sensor combination on the Essentials 2MP Mini-Dome switches the camera automatically between color and black and white mode in a feature known as True Day/Night. Regardless of the ambient illumination level, the camera is able to maintain crystal clear images in low light scenarios.

Balance Images with Wide Dynamic Range

The difference in extreme lighting within a scene is known as dynamic range. Cameras with the Wide Dynamic Range functionality have special software that allows them to balance foreground and background lighting for one clear image. This makes them ideal for recording areas like store entrances where the contrast between the sunshine outside and the dim lighting inside can be extremely difficult to record.

The Illustra Essentials 2MP Mini-Dome camera takes advantage of the latest pixel-by pixel dynamic range offered today. Maintain facial details with whole scene clarity by working within the megapixel lens to enhance the precision of the images for a high resolution HD solution that excels in an array of challenging lighting conditions.

Specifications

Operational	
Resolution & Aspect Ratio	1920 x 1080 (1080p) 16:9
Max Frame Rate	30fps
Video Compression	H.264, H.264+ IntelliZip, H.265, H.265+ IntelliZip, MJPEG
Video Streams	Dual Stream with both streams at a maximum of 1080p @ 30ips
Imager	1/2.8", Sony CMOS
S/N Ratio	More than 50dB
Image Orientation Settings	Off, flip, mirror, both
Lens Type	Fixed 2.8mm
Focus Control	Factory Focused
Aperture	F/1.8
Field of View (H/V)	110°/60°
Chuttar Caaad	1/2~1/10,000s (Manual:default NTSC=1/30s, PAL=1/25s) /
Shutter Speed	(Shutter-priority:default NTSC=1/60s, PAL=1/50s)
Minimum Illumination	
Color	0.08 Lux (50IRE) 0.03 Lux (30IRE)
B/W	0.05 Lux (50IRE) 0.02 Lux (30IRE)
With IR	0.0 Lux
IR LEDS	Yes
IR Distance	25m
Noise Reduction	3D
Wide Dynamic Range	True WDR 120dB
Day/Night	True Day/Night with ICR
ONVIF-Compliant	Profile S/G/Q
Motion Detection Zones	3
Blur Detection Zones	Yes
Privacy Zones	8
Image Rotation	Corridor
Analog Video Output	No
Audio	No
Simultaneous Users	5





Network	
Ethernet Interface	IEEE 802.3, 10/100 Base-T/TX, auto sensing, 1 x RJ45
	TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, TLS, Unicast, NTP,
Supported Protocols	SMTP, WSSecurity, IEEE 802.1x, PEAP, SSH, HTTPS, SSL, SOAP, WSAddressing, SNMP, UPnP, RTSP,
	LLDP
Configuration Management	
Web Browser	IE 11 or above, Firefox, Chrome, Safari, Microsoft Edge
	IEEE 802.1X
Security	HTTPS
	Digest authentication, IP address filtering
Onboard Storage	00.00
Card Support	SDXC up to 256GB
Pre-Alarm Recording	1-10 sec
Recording Format	AVI
Playback	Via Web Browser
Recording Trigger	Blur Detection, Motion Detection
VideoEdge TrickleStor	Yes
Electrical	
Power Input	DC12V; PoE IEEE 802.3af Class 3
Maximum Power Draw	7.3W
Physical	
Dimensions (WxH)	Ø110mm x 82mm (Ø4.33in x 3.29in)
Weight	0.53kg (1.16 lbs)
Housing Color	White, RAL 9003
Operating Temperature	Cold Start Temperature: -20°C to 60°C (-4°F to 140°F)
	Operating Temperature: -30°C to 60°C (-22°F to 140°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	Desiccant pack provided
Vandal Resistant	IK10
Outdoor Rating	IP67
Regulatory Safety	III 62260 1 IEC 62260 1 EN 62220 1 IEC 62471
Emissions	UL 62368-1, IEC 62368-1, EN 62338-1, IEC 62471 FCC CFR 47, Part 15 Class A, EN 55032
Immunity	EN 50120-4 EN 61000-2-2 EN 61000-2-2
Environment	RoHS, Reach, WEEE
NDAA Compliant	Yes
INDAA COMPHANT	res

Ordering Information

Model	Description
IES02-D10-OI04	Illustra Essentials Gen4 2MP Dome, 2.8mm, IP67, IK10, Clear Bubble, White, True D/N with IR, True WDR, PoE/12VDC

Ordering Information

Model	Description
IA-ADP-iS-E40	Pendant Cap Adapter Plate





About Johnson Controls

At Johnson Controls (NYSE:JCI), we transform the environments where people live, work, learn and play. As the global leader in smart, healthy and sustainable buildings, our mission is to reimagine the performance of buildings to serve people, places and the planet.

Building on a proud history of nearly 140 years of innovation, we deliver the blueprint of the future for industries such as healthcare, schools, data centers, airports, stadiums, manufacturing and beyond through OpenBlue, our comprehensive digital offering.

Today, with a global team of 100,000 experts in more than 150 countries, Johnson Controls offers the world's largest portfolio of building technology and software as well as service solutions from some of the most trusted names in the industry.

Visit www.johnsoncontrols.com for more information and follow @JohnsonControls on social platforms.

© 2023 Johnson Controls. All rights reserved. Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative

IL1426-DS-202303-R05-HS-EN



